


VRL5 92-HS (6-QTF-92)



Dimensions (mm)



Physical Specification (mm)


Nominal Voltage	12V	
Nominal Capacity(20HR)	95Ah	
Dimension	Length	353 +0/-2mm(13.9inches)
	Width	175 +0/-2mm(6.89inches)
	Container Height	190 +0/-3mm(7.48inches)
	Total Height(with Terminal)	190 +0/-3mm(7.48inches)
Weight	Approx 27.3Kg(60.20lbs)	
Standard Terminal	1	
Cell layout	0	
Hold-Down	B13	
Cell plate qty	1	
Case	Black-PP Material	
Cover	Black-PP Material	
Handle	Black-PP Material	

Electrical Specification

Rated Capacity	20 hour rate(4.75A)	95Ah
Reserve Capacity		160min
Cold Cranking Performance Amps@0°F(-18°C)		850A

Standard Terminal (mm)

Terminal Type	D	
	Positive	Negative
1	19.5 ⁰ _{-0.3}	17.9 ⁰ _{-0.3}



Cell Layout



Figure(0)

Discharge Characteristics(-18°C,0°F)

AGM-L5(CCA-SAE)
(CCA-SAE)Capacity Test(@-18)with I=850A
Spec U_{10S} ≥ 7.5V U_{30S} ≥ 7.2V

